

ACCESSORIES

Cable Weight, Hub Assembly, Float Bracket, Cable Connectors, Cord Seal, Cable Clamp Assembly, Pressure Transducers, Anchor, Chain, and Vertical Reed Switch.

CABLE WEIGHT

Provides an accurate pivot point for suspended float switches.

- Gripper teeth on clip and weight channel securely lock float cable into place
- Cable Weight can be adjusted without the use of tools



U.S. Patent 5,306,885

HOUSING: 1 pound, 12 ounce (0.8 kgs.), 2.8 inch diameter x 3.3 inch long (7.1 cm diameter x 8.4 cm), impact resistant, non-corrosive, PVC housing for use in liquids up to 140°F (60°C)

CLIP: injection molded acetal plastic

WIRE/CABLE ACCOMMODATED: SJOW, SJTW, 18/2, 18/3, 16/2, 16/3, 14/2 and 14/3

HUB ASSEMBLY

Provides liquid-tight conduit attachment location.

- Available in 1, 1.5 and 2 inch sizes.
- UL Listed and CSA Certified terminal adapter



TERMINAL ADAPTER (HUB): PVC

GASKET: neoprene

LOCK NUT: metal

CABLE CONNECTORS

Provides strain relief and a liquid-tight seal.

- UL Listed and CSA Certified



VDE Approved

ROUND CABLE SPECIFICATIONS

MATERIAL: polyimide flame-resisting, self-extinguishing plastic

ORING: neoprene plastic

HOLE REQUIREMENT: NPT threaded OR clearance holes (jam nut included)




RCC-8

NPT Hub: .5 inch (1.27 cm)

Maximum Diameter: .480 inch (1.22 cm)

Minimum Diameter: .270 inch (.68 cm)

Wire/Cable (AWG) Accommodated: 18/2, 18/3, 18/4, 16/2, 16/3, 16/4, 14/2, and 14/3



RCC-12

NPT Hub: .75 inch (1.90 cm)

Maximum Diameter: .709 inch (1.80 cm)

Minimum Diameter: .545 inch (1.38 cm)

Wire/Cable (AWG) Accommodated: 14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2, and 10/3

RCC-16

NPT Hub: 1.0 inch (2.54 cm)

Maximum Diameter: .98 inch (2.49 cm)

Minimum Diameter: .71 inch (1.80 cm)

Wire/Cable (AWG) Accommodated: Round cable with outside diameter within range identified above.

FLOAT BRACKET

Provides convenient installation of float switches.

- Six Float Bracket supports 1-6 floats
- Four Float Bracket supports 1-4 floats
- Can be directly mounted to wall or used with wall mounting device
- Provides convenient location to stow excess float cord
- Supplied with UL Recognized cord strain relief connectors



METAL COMPONENTS: all metal components are made of 300 series stainless steel

STRAIN RELIEF CONNECTORS: which accommodate 18/2, 18/3, 16/2, 16/3 SJOW and SJTW cords

FLAT UF CABLE SPECIFICATIONS

MATERIAL: weather-stabilized thermo plastic

ORING: neoprene plastic

HOLE REQUIREMENT: NPT threaded OR clearance holes (jam nut included)




UFCC-8

NPT Hub: .50 inch (1.27 cm)

Maximum: .26 x .56 inch slot

Wire/Cable (AWG) Accommodated: 14/2, 12/2, 10/2



UFCC-12

NPT Hub: .75 inch (1.90 cm)

Maximum: .26 x .60 inch slot

Wire/Cable (AWG) Accommodated: 14/3, 12/3

PRODUCTS CONTINUED ON NEXT PAGE.

SJE Rhombus

PO Box 1708, Detroit Lakes, MN 56502

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: sje@sjerhombus.com

www.sjerhombus.com